

Item 7113591



The Flex 75 Side floor drain has a 75mm side outlet and the floor drain can be cut to adjust the overall height. To reduce the height, unscrew the flange, cut the ribbed part of the floor drain body to the desired size and then return the o-ring. The floor drain is suitable for installation in wooden or concrete joists. The Flex floor drain comes complete with a removable water trap, clamping ring and plastic grate. It also comes with a protective cover that is intended to prevent any concrete or debris from installation from entering the drain.

The automatic clamping ring is used for both sealing membrane and vinyl flooring. It is a self-adjusting clamping ring for vinyl flooring with a thickness of 1,5 mm to 2 mm.

Specifications

The Flex 75 Side floor drain has a 75mm side outlet and the floor drain can be cut to adjust the overall height. To reduce the height, unscrew the flange, cut the ribbed part of the floor drain body to the desired size and then return the o-ring. The floor drain is suitable for installation in wooden or concrete joists. The Flex floor drain comes complete with a removable water trap, clamping ring and plastic grate. It also comes with a protective cover that is intended to prevent any concrete or debris from installation from entering the drain.

The automatic clamping ring is used for both sealing membrane and vinyl flooring. It is a self-adjusting clamping ring for vinyl flooring with a thickness of 1,5 mm to 2 mm.

Item Number	7113591
--------------------	---------

Dimension	Ø75 mm
------------------	--------

Floor Construction	Concrete/Wood
Floor Covering	Concrete/Resin/Tiles/Vinyl
Function	Side outlet
Item Color	White
Material	PP
Pressure Flow Temp	1,4 l/s
Size	Ø150 mm
Version	With plastic grating