

Item 7113764UK



The Minimax 50 floor drain has a 50 mm side outlet and a low total height of just 76mm. It is suitable for installation in concrete joists, as well as wooden joists when using a former tray or the Purus Plate. The Minimax 50 floor drain comes complete with a removable NOOD water trap, clamping ring, 50 mm to 1½" adapter for solvent weld and plastic grate for vinyl flooring. The NOOD water trap is a mechanical trap which closes when there is no water present, thus preventing any foul air from escaping through the drain. The floor drain is suitable for vinyl, tiled and resin flooring. Grates for tiled and resin floors are ordered separately.

The automatic clamping ring is used for both sealing membrane and vinyl flooring. It is a self-adjusting clamping ring for vinyl flooring with a thickness of 1,5 mm to 2 mm.

Specifications

The Minimax 50 floor drain has a 50 mm side outlet and a low total height of just 76mm. It is suitable for installation in concrete joists, as well as wooden joists when using a former tray or the Purus Plate. The Minimax 50 floor drain comes complete with a removable NOOD water trap, clamping ring, 50 mm to 1½" adapter for solvent weld and plastic grate for vinyl flooring. The NOOD water trap is a mechanical trap which closes when there is no water present, thus preventing any foul air from escaping through the drain. The floor drain is suitable for vinyl, tiled and resin flooring. Grates for tiled and resin floors are ordered separately.

The automatic clamping ring is used for both sealing membrane and vinyl flooring. It is a self-adjusting clamping ring for vinyl flooring with a thickness of 1,5 mm to 2 mm.

Item Number	7113764UK
Dimension	Ø50 mm
Floor Construction	Concrete flooring
Floor Covering	Tiles
Function	Side outlet
Item Color	White
Material	PP
Pressure Flow Temp	0,8 l/s
Size	Ø130 mm
Version	With NOOD water trap