



## Item 7113764UK

The Minimax 50 floor drain has a 50 mm side outlet and a low total height of just 76mm. It is suitable for installation in concrete joists, as well as wooden joists when using a former tray or the Purus Plate. The Minimax 50 floor drain comes complete with a removable NOOD water trap, clamping ring, 50 mm to 1½" adapter for solvent weld and plastic grate for vinyl flooring. The NOOD water trap is a mechanical trap which closes when there is no water present, thus preventing any foul air from escaping through the drain. The floor drain is suitable for vinyl, tiled and resin flooring. Grates for tiled and resin floors are ordered separately.

The automatic clamping ring is used for both sealing membrane and vinyl flooring. It is a self-adjusting clamping ring for vinyl flooring with a thickness of 1,5 mm to 2 mm.



EPD®  
THE INTERNATIONAL EPD® SYSTEM

## Specifications

|                           |                   |
|---------------------------|-------------------|
| <b>Item Number</b>        | 7113764UK         |
| <b>Floor Construction</b> | Concrete flooring |
| <b>Floor Covering</b>     | Tiles             |

|                               |                      |
|-------------------------------|----------------------|
| <b>Function</b>               | Side outlet          |
| <b>Item Color</b>             | White                |
| <b>Material</b>               | PP                   |
| <b>Outlet Dimension</b>       | Ø50 mm               |
| <b>Pressure Flow<br/>Temp</b> | 0,8 l/s              |
| <b>Size</b>                   | Ø130 mm              |
| <b>Version</b>                | With NOOD water trap |

