PURUS



Item 818902

Purus channel combo is made of acidresistant stainless steel with side outlet Ø110 mm for installation in concrete. The floor channel is 300x300x200 and is intended for concrete flooring. There is always residual water in the channel about 50 mm of water forms the water trap in the bottom of the channel and is equipped with a cleaning plug. The floor channel requires an almost continuous flow to function properly. Unsuitable in environments that set hygiene requirements.

Item 818906

Purus channel combo is made of acidresistant stainless steel with side outlet Ø110 mm for installation in concrete. The floor channel is 500x300x200 och är avsedd för betonggolv som ytskick. There is always residual water in the channel about 50 mm of water forms the water trap in the bottom of the channel and is equipped with a cleaning plug. The floor channel requires an almost continuous flow to function properly. Unsuitable in environments that set hygiene requirements.

Specifications

Floor Covering

Item Number	818902
Dimension	Ø110 mm
Floor Construction	Concrete flooring

Concrete

Function	Side outlet	
Item Color	Stainless	
Material	Acid-resistant stainless steel 1.4404	
Pressure Flow Temp	3,4 l/s	
Size	300x300x200 mm	
Surface	Pickled	
Version	Do not forget grid/grating	
Item Number	818906	
Dimension	Ø110 mm	
Floor Construction	Concrete flooring	
Floor Covering	Concrete	
Function	Side outlet	
Item Color	Stainless	
Material	Acid-resistant stainless steel 1.4404	
Pressure Flow Temp	3,4 l/s	
Size	500x300x200 mm	
Surface	Pickled	
Version	Do not forget grid/grating	

Dimension (mm)	LxWxH (mm)	Ø (mm)
300x300x150	303 x 303 x 150	75
300x300x200	303 x 303 x 200	110
500x300x150	503 x 303 x 150	75
500x300x200	503 x 303 x 200	110



