

## Item 855656



Purus channel spalte module 75 is a floor channel made of acid-resistant stainless steel for installation in concrete. The floor channel is intended for concrete, epoxy and tile floors without a waterproofing membrane. Purus channel spalte module is only 20 mm wide, has a built-in fall of which the height is 75 mm and length 500x500 mm. Purus channel spalte module is delivered with gasket and screw connection for installation but needs to be supplemented with grid depending on the environment and outlet house. The total height with screw joints is 124 mm.

## Item 855657

Purus channel spalte module 90 is a floor channel made of acid-resistant stainless steel for installation in concrete. The floor channel is intended for concrete, epoxy and tile floors without a waterproofing membrane. Purus channel spalte module is only 20 mm wide, has a built-in fall of which the height is 90 mm and length 500x500 mm. Purus channel spalte module is delivered with gasket and screw connection for installation but needs to be supplemented with grid depending on the environment and outlet house. The total height with screw joints is 124 mm.

## Item 855658

Purus channel spalte module 105 is a floor channel made of acid-resistant stainless steel for installation in concrete. The floor channel is intended for concrete, epoxy and tile floors without a waterproofing

membrane. Purus channel spalte module is only 20 mm wide, has a built-in fall of which the height is 105 mm and length 500×500 mm. Purus channel spalte module is delivered with gasket and screw connection for installation but needs to be supplemented with grid depending on the environment and outlet house. The total height with screw joints is 124 mm.

## Specifications

Purus channel spalte module 75 is a floor channel made of acid-resistant stainless steel for installation in concrete. The floor channel is intended for concrete, epoxy and tile floors without a waterproofing membrane. Purus channel spalte module is only 20 mm wide, has a built-in fall of which the height is 75 mm and length 500×500 mm. Purus channel spalte module is delivered with gasket and screw connection for installation but needs to be supplemented with grid depending on the environment and outlet house. The total height with screw joints is 124 mm.

<b>Item Number</b>	855656
<b>Floor Construction</b>	Concrete flooring
<b>Floor Covering</b>	Concrete/Resin/Tiles
<b>Item Color</b>	Stainless
<b>Material</b>	Acid-resistant stainless steel 1.4404
<b>Size</b>	500×500 mm
<b>Surface</b>	Pickled
<b>Version</b>	20 mm gap, without grate
<b>Item Number</b>	855657
<b>Floor</b>	Concrete flooring

<b>Construction</b>	
<b>Floor Covering</b>	Concrete/Resin/Tiles
<b>Item Color</b>	Stainless
<b>Material</b>	Acid-resistant stainless steel 1.4404
<b>Size</b>	500×500 mm
<b>Surface</b>	Pickled
<b>Version</b>	20 mm gap, without grate
<b>Item Number</b>	855658
<b>Floor Construction</b>	Concrete flooring
<b>Floor Covering</b>	Concrete/Resin/Tiles
<b>Item Color</b>	Stainless
<b>Material</b>	Acid-resistant stainless steel 1.4404
<b>Size</b>	500×500 mm
<b>Surface</b>	Pickled
<b>Version</b>	20 mm gap, without grate